

REDUCE PART MARKING

WILA ROTABEND®



WILA ROTABEND

WILA prides itself on producing the finest quality and highest precision press brake tooling, and it makes no exception with its new line of rotating v dies, RotaBend. With tight tolerances and CNC Deephardened contact surfaces and rotor wings, you can now easily bend short flanges and reduce part marking without sacrificing the WILA quality and precision you've come to expect.

WILA RotaBend includes replaceable built-in inserts that rotate to enable forming of short or tapered flanges.

Advantages of WILA RotaBend:

- Eliminate distortion at holes near the bend line,
- Reduces part marking,
- Forms very tight inside radius when required,
- Rotor wings and contact surface of the body are hardened ensuring long term durability and accuracy,
- Rotor wings are very easy to disassemble and clean,
- Machined to extremely tight tolerances for ultimate precision,
- Narrow tool design for down flange bending freedom,
- Bend parts of various material thickness with same tool,
- Can be combined with OM tools for bending 90° angles.



THREE DIFFERENT MODELS

WILA introduces its line of RotaBend, available in three models for bending up to 6mm material thickness.

OZU-WRB-301



OZU-WRB-302



OZU-WRB-303






	OZU-WRB-301	OZU-WRB-302	OZU-WRB-303
Max. material thickness	2 mm	3 mm	5 mm
Wing rotor opening	8.9 mm	12.9 mm	26.3 mm
Max. punch radius	2.4 mm	3 mm	6 mm
Min. outside flange length*	5.2 mm (S=1mm)	6.5 mm (S=1 mm)	15.5 mm (S=2 mm)
Return bend (outside dimension)	14.4 mm (S=1mm)	20 mm (S=1 mm)	35 mm (S=2 mm)
Min. bend angle**	40°	40-60° (40° max. S=2 mm)	60° (max. S=4 mm)
Hardness of wing rotor	56-60 HRC	56-60 HRC	56-60 HRC
Hardness of body contact surface	52-54 HRC	52-54 HRC	52-54 HRC
Working height***	100 mm	100 mm	100 mm
Bottom adaption width	13 mm	13 mm	13 mm
Tonnage capacity	100 t/m	130 t/m	200 t/m
Available lengths	515 mm 550 mm sectioned 200 mm 100 - 100 mm	515 mm 550 mm sectioned 200 mm 100 - 100 mm	515 mm 200 mm 100 - 100 mm

* These dimensions are outside dimensions and apply to bending mild steel at 90°. Dimensions can change with stainless steel and aluminum.

** Minimum bend angle may vary depending material and punch radius.

*** Can be combined with OM tools for bending 90° angles.



WILA. THE PRESS BRAKE PRODUCTIVITY PEOPLE.

WILA is totally focused on providing a line of products and support systems to maximize the productivity of your press brakes. For over 80 years, WILA has specialized in Clamping Systems, Crowning Systems and Tooling and Accessories to reduce set-up time and improve accuracy of the press brake. Through strong partnerships with the world's leading press brake manufacturers, an extensive and trained dealer network, long experienced regional managers, dedicated application support and engineering staff, WILA is always close at hand to support your needs.

WILA B.V.

P.O. box 60

NL-7240 AB Lochem

The Netherlands

Phone +31 (0)573 28 98 00

Phone sales +31 (0)573 28 98 50

E-mail: info@wila.nl



PRESS BRAKE PRODUCTIVITY CATALOG

Request a copy of the Press Brake Productivity Catalog
at www.wila.nl

www.wila.nl

 **WILA**
SINCE 1932
THE PRESS BRAKE PRODUCTIVITY PEOPLE